

Working Load Limit (WLL) for chain sling 1-4 part, Grade 80 and 100

GRADE 80	1-part	2-Part 0°-45°	2-Part 45°-60°	3/4-Part 0°-45°	3/4-Part 45°-60°
	WLL (ton)	WLL (ton)	WLL (ton)	WLL (ton)	WLL (ton)
Chain sling 6 mm	1,12	1,60	1,12	2,36	1,70
Chain sling 7mm	1,50	2,12	1,50	3,15	2,24
Chain sling 8 mm	2,00	2,80	2,00	4,25	3,00
Chain sling 10 mm	3,15	4,25	3,15	6,70	4,75
Chain sling 13 mm	5,30	7,50	5,30	11,20	8,00
Chain sling 16 mm	8,00	11,20	8,00	17,00	11,80

GRADE 100	1-Part	2-Part 0°-45°	2-Part 45°-60°	3/4-Part 0°-45°	3/4-Part 45°-60°
	WLL (ton)	WLL (ton)	WLL (ton)	WLL (ton)	WLL (ton)
Chain sling 6 mm	1,40	2,00	1,40	3,00	2,10
Chain sling 8 mm	2,50	3,50	2,50	5,30	3,80
Chain sling 10 mm	4,00	5,60	4,00	8,00	5,70
Chain sling 13 mm	6,70	9,40	6,70	14,00	10,00
Chain sling 16 mm	10,00	14,00	10,00	21,20	15,00

We reserve the right to adjust the values in the tables above.